61826 Installation Guide

Prone Leg Curl

Catalog

Introduction	----------	2
Assembling	----------	3
Accessory List	----------	12

Introduction

Please take the time to carefully read the instructions before installing .Please refer to the manual to determine the list of all components were packaged well, . (If there have some parts missed or damaged please immediately call our customer service department) Please refer to the installation instruction while installing.

This device designed to provide the most effective and smoothest training movements. After installing, you can only know how to use the products after you know all the functions. If there is any question, please check the installation instruction and find out the wrong steps during the installing. If still not work, please contact the distributors authorized by original factory. The code and manual will be needed.

Tools

Rubber Rod
Level Ruler
Octagonal wrench
More than 2 person
Spring Clamp
Adjustable wrench

Assembling

Step 1: Connect the horizontal strand two-head connection frame 1 (M2) with the connection frame 2 (M3) and the side frame (M0) by the following method.
• 4 x Hexagon socket cheese head screws (M24)
• 4 x Spring washers (M4) • 4 x Flat washers (M5)
Step 2: Connect the connecting lower shield (M6) to the counterweight frame (M1) using the following method.
• 2 x Hexagon socket cheese head screws (M7)
Step 3: Install The 2 counterweight frame feet (M8) to the counterweight frame (M1)



Assembling

Step 4: Connect the horizontal strand two-headed side frame (M0) with the connection frame 1 (M2) by the following method.
• 8 x Hexagon socket cheese head screws (M1)
• 4 x Spring washers (M4)
• 4 x Flat washers (M5)
Step 5:Install 2 Flat rear feet (M10) to the horizontal strand 2 head side frame (M0).



Assembling

Step 6: Connect the horizontal strand two-head connection frame 11 (M11) with the connection frame 1 (M2) and the side frame (M0) by the following method.
• 4 x Hexagon socket cheese head screws (M1)
• 4 x Spring washers (M4)
• 4 x Flat washers (M5)
• 2 x Hexagon socket cheese head screws (M12)

Assembling

Step 7: Connect the horizontal strand two-headed seat cushion (M13) with the horizontal strand two-head connection frame 2 (M3) by the following method.
• 2 x Hexagon socket cheese head screws (M14)
Step 8: Attach 1 hole plug (M15) to the horizontal strand 2 head side frame (M0).
Step 9: Attach 2 hole plugs (M16) to the horizontal strand two-head connection frame 11 (M11).



Assembling

Step 10: Connect the horizontal strand two-head force arm (M18) and flange (M17) with the horizontal strand two-head connecting frame 1 (M2) by the following method.
• 2 x Hexagon socket flat countersunk head screws (M19)
Step 11: Connect the two ends of the 120 cable (M20) by the following method.
Attach the cable to the horizontal delishedd force arm (M18) using the following method.
• 1 x Hexagon socket flat countersunk head screws (M19)
• 1 x 6061aluminum cap (M39)

Assembling

Step 12: Slide the two counterweight rubber pads (M22) into the two guide bars (M22).
Connect the counterweight block pin (M23) to the guide bar (M22) and plane them in the counterweight lower shield (M6) to the guide bar (M22) by the following method.
• 2 x Hexagon socket cheese head screws (M25)
Step 13:Install the 16 counterweight (M26) onto the guide bar (M22) with the isolation tube facing up.
Install the guide block bolt (M27) to the guide bar (M22).
Insert the counterweight block pin (M23) into the counterweight block (M26).
Step 14: Attach the guide bar fixing plate (M28) to the guide bar (M22).
Attach the guide bar fixing plate (M28) to the counterweight frame (M1) using the following method.
• 2 x Hexagon socket cheese head screws (M31)
Tighten the bolt with a wrench, then proceed to the next step

Assembling

Step 16: Disassemble the pre-assembled 95 and 120 wire reels first, thread in the wire rope (M32) as shown, Connect the 120 cable (M20) and 2 quick hooks (M34) to the horizontal strand two-head connection frame 2 (M3) using the following method:
• 1 x Wire rope (M32) • 2 x Wire steel line fastener (M33)
Note that these spools are installed in tandem with the wire rope (M32).
Thread the wire rope (M32) over the top of the 120 wire reel flange (M21) first, and the other end to the counterweight frame (M1) inside.

Assembling

Step 16:Slide the two rib strips (M38) into the two baffles (M37)
and attach them to the counterweight frame (M1) using the baffle pressure plate.
Slide the trim plate (M36) into the two baffles (M37) and
attach to the counterweight frame (M1) using the baffle pressure plate.
Attach the two upper shrouds (M40) to the counterweight frame (M1) using the following method.
• 2 x Hexagon socket cheese head screws (M41)
Step 17: Connect the two counterweight rivet plugs (M42)
to the counterweight frame (M1) using the following method.
• 2 x Hexagon socket cheese head screws (M41)
Step 18: Snap the top cover of the upper shroud (M42) to the upper shroud (M40).

Assembling

Important Tips

Now that Prone leg curl is assembled, you need to take a moment to make sure your machine is ready for workouts. Check to make sure that the guide bar is vertical in both directions. If that are not plumb you must loosen some of the frame hardware and reassemble and tighten the bolts.

Accessory List

NO	Name and specification	Quantity
1	Counterweight frame	1
2	connection frame 1	1
3	Hexagon socket cheese head screws (M24*M25)	10
4	Spring washers (M5)	12
5	Flat washers (M5)	12
6	Counterweight lower shroud	1
7	Hexagon socket cheese head screws (M24*M5)	12
8	Counterweight frame foot pads	2
9	side stand	2
10	Flat Oval Footbed	2
11	connection frame 2	1
12	Hexagon socket cheese head screws (M24*M5)	2
13	seat cushion	1
14	Hexagon socket cheese head screws (M24*M5)	3
15	Hole Plug	3
16	Force Arm	1
17	Flanges	1
18	Hexagon socket flat countersunk head screws (M24*M25)	3
19	6061aluminum cap	2
20	7061aluminum cap	1
21	Leg press frame	1

Accessory List

NO	Name and specification	Quantity
22	Universal counterweight guide rod	2
23	Counterweight rubber pad	2
24	Counterweight stand base	2
25	Hexagon socket cheese head screws (M24*M25)	4
26	Spring washers (M)	2
27	Flat washers (M)	2
28	Counterweight block	16
29	Guide block set	1
30	Guide bar fixing plate	1
31	Counterweight pins	1
32	Cable	1
33	120 wire wheels	1
34	Wire wheel box	2
35	Wire wheel box bushings	2
36	Wire spool	1
37	Baffle	4
38	Counterweight source decorative strips	2
39	Counterweight source decorative strips	1
40	Counterweight upper shield	2
41	Counterweight rivet plug cover	2
42	Upper shroud top cover	1

* Pre-assembled parts are not listed in this table.