

Model:T320 1

Catalogue

Brief ····· 2
Underframe Installation ····· 4
Force Arm Installation ····· 5
Slideway Installation ····· 6
Gas Rod & Pedal Installation ····· 7
Cable Installation ····· 8
Cover Installation ····· 9
Accessories List ····· 10

Model:T320 2

Brief

Please take the time to carefully read the instruction before installing.Please refer to the manual to determine the list of all components were packaged well. (If there have some parts mixed or damaged please immediately call our customer service department).Please refer to the installation instruction while installing.

This device designed to provide the most effective and smoothest training movements. After installing, you can only know how to use the products after you have all the functions. If there are any questions, please check the installation instruction and find out the wrong steps during the installing. If still not work, please contact the distributors authorized by original factory. The code and manual will be needed.

Tools

Rubber stick
Levelling instrument
Circlip pliers
Socket head screw wrench
The adjustable wrench
More than 2 person

Model:T320 3

Underframe Installation

CAUTION:
Tie wrench used to tighten the hardware



Important Notification:
All fit Products with balance weight, please put the lower cover in the balance weight frame before installing the connecting rack .

Model:T320 4

Force Arm Installation

CAUTION:
Tie wrench used to tighten the hardware



Model:T320 5

Slideway Installation

CAUTION:
Tie wrench used to tighten the hardware



Model:T320 6

Gas Rod & Pedal Installation

CAUTION:
Tie wrench used to tighten the hardware



Model:T320 7

Cable Installation

Step testing:
Loose the safety nut and whole glute bolt to the proper location to cable



Important Notification:
Please read the T300-Installation Instruction as the reference to install the balance weight frame and required accessories.

Model:T320 8

Cover Installation

Important Notification:
Not T320 has been assembled, the balance weight frame is to make sure over driver is square and vertical. With a spirit level to check whether the guide bar perpendicular in the two directions. If not, then you have to loose some of the vertical frame removable hardware and tighten the screw.

Model:T320 9

Accessories List

Caution:Some spare parts which have been assembled are not in the list

No.	Name & Specification	Material	Qty.
1	Balance Weight Frame	Steel	1
2	Underframe	Steel	1
3	Hexagon socket button head screws(M10*30)	45	4
4	Silicone rubberstrip cover	SILICONE	4
5	Inner hexagon countersunk head screws(M8*20)	45	2
6	Cover	Steel	1
7	Front cap	Plastic	2
8	Counterweight	45	1
9	Hexagon socket head cap screws(M10*40)	45	2
10	Flange	Nylon	2
11	Deep Groove Ball Bearing 61908	Bearing steel	2
12	Main spool	45	1
13	Installing cover	SILICONE	1
14	Inner hexagon countersunk head screws(M8*45)	45	2
15	Main Rope pressing plate-1	Q235	1
16	Inner hexagon countersunk head screws(M8*30)	45	1
17	Main Rope fixed shaft	45	1
18	Main Rope pressing plate-2	Q235	1
19	Inner hexagon countersunk head screws(M8*25)	45	2
20	Bearing installing pad	SILICONE	1
21	Deep Groove Ball Bearing 61906	Bearing steel	2
22	Deep Groove Ball Bearing 6200	Bearing steel	2
23	M10 Big gasket	45	2
24	Hexagon socket button head screws(M10*25)	45	2
25	Bearing installing pad	SILICONE	1
26	Deep Groove Ball Bearing 61906	Bearing steel	2
27	Bearing pedrs	Plastic	2
28	Deep Groove Ball Bearing 6203	Bearing steel	2
29	M8 Nut cover	Plastic	2
30	Silkbag cap	45	2

Model:T320 10

Accessories List

Caution:Some spare parts which have been assembled are not in the list

No.	Name & Specification	Material	Qty.
31	Silkbag nut rubber pad	Rubber	2
32	Eye Nut-T320	Plastic	2
33	Eye Nut fixed bar	45	2
34	Hexagon socket button head screws(M8*20)	45	2
35	Pedal	Galvanized	2
36	5X45 Pins set	Rubber	2
37	T20 line of shorter	Plastic	2
38	Wire Rope	Plastic	2